



# Safety data sheet

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 1. Identification of the substance/preparation and of the company/undertaking

Revision: 15-02-2010/ MJH Replaces: 10-11-2009	Distributor: <b>ITW Chemical Products Scandinavia</b> <b>Priorsvej 36</b> <b>8600 Silkeborg</b>
<b>Product use:</b> Lubricating compound spray.	
<b>Article no.:</b> 14265	<b>Tel:(+45) 86 82 64 44 Fax:(+45) 86 82 64 64</b> <b>Emergency telephone number: +45 86 82 64 44</b> <b>Emergency telephone number between 8 and 15.30 ;</b> <b>Monday to Friday.</b> <b>Contact person:Marlene Hesselberg</b> <b>Email: info@itw-scan.com</b>

### 2. Hazards identification

Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
<b>Additional information</b> Prolonged or repeated inhalation of vapours may cause damage to the central nervous system.

### 3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	Classification	w/w%	
265-149-8	64742-47-8	Distillates (petroleum), hydrotreated light	Xn;R65 R66	5-10	3
265-151-9	64742-49-0	Naphtha (petroleum), hydrotreated light	F; R11 Xn;R65 Xi;R38 N;R51/53 R67	10-25	3
270-704-2	68476-85-7	Petroleum gases, liquefied	F+;R12	25-50	
231-096-4	7439-89-6	Iron	F;R11	1-5	
292-460-6	90622-58-5	Aliphatic hydrocarbon	Xn; R65, R66	1-5	3
215-222-5	1314-13-2	zinc-oxide-	N;R50/53	1-5	

3) R65 is not applicable due to use as aerosols.  
Please see section 16 for the full text of the R-phrases

ITW Chemical Products Scandinavia Priorsvej 36, 8600 Silkeborg +45 86 82 64 44/+45 86 82 64 64

Revision: 15-02-2010/MJH  
Replaces: 10-11-2009

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 4. First aid measures

**Inhalation**

Remove the exposed person to fresh air. If symptoms persist seek medical advice.

**Ingestion**

Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice if symptoms persist.

**Skin**

Remove contaminated clothing. Wash skin with soap and water. Seek medical advice if symptoms persist.

**Eyes**

Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.

**Burns**

Flush with water until pain ceases. Remove clothing that is not stuck to the skin – seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

**Other information**

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

### 5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water spray, as it may spread the fire. Use water or water mist to cool non-ignited stock. Remove containers from the danger area if this is possible without risk. ATTENTION! Spray cans may explode.

### 6. Accidental release measures

Provide adequate ventilation. Smoking and naked flames prohibited. Wipe up drops and splashes with a cloth and dispose of the cloth as set out in section 13.

### 7. Handling and storage

**Handling**

Please see item 8 for information on personal protection. Smoking and naked flames prohibited.

**Storage**

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Do not expose to heat (e.g. sunlight).

ITW Chemical Products Scandinavia Priorsvej 36, 8600 Silkeborg +45 86 82 64 44/+45 86 82 64 64

Revision: 15-02-2010/MJH  
Replaces: 10-11-2009

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 8. Exposure controls/ personal protection

#### Precautions for use

Work under effective process ventilation (e.g. local exhaust ventilation). Smoking and naked flames prohibited. Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work.

#### Respiratory protection

In case of insufficient ventilation, wear respiratory protective equipment with filter A.

#### Gloves and protective clothing

Wear protective gloves made of nitrile rubber.

#### Eye protection

Wear safety goggles if there is a risk of eye splash.

#### Occupational exposure limits

Ingredients	Exposure limit	Remarks
zinc-oxide-	- ppm 5 mg/m <sup>3</sup>	-

#### Control methods

Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

### 9. Physical and chemical properties

State: Aerosol

Solubility in water: Insoluble

Odour: Characteristic

### 10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions. Avoid heating and contact with ignition sources. Durability for the aerosol is at least 5 years from date of production, if there is enough propellant in the aerosol to apply the contents in a satisfactory way.

### 11. Toxicological information

#### Acute

##### Inhalation

The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. Inhalation of spray mist may cause chemical pneumonia.

##### Ingestion

Spray mist in mouth may irritate mucous membranes in mouth and throat.

##### Skin contact

Irritating to skin – may cause reddening.

##### Eye contact

May cause eye irritation.

#### Long-term effects

##### May cause damage to the central nervous system

Prolonged or repeated inhalation of vapours may cause damage to the central nervous system.

Revision: 15-02-2010/MJH  
Replaces: 10-11-2009

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 12. Ecological information

Avoid unnecessary release to the environment.

#### Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 13. Disposal considerations

Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility with the specifications set out below.

Empty aerosols (totally emptied for propellant) or aerosols that by accident have been punctured: EWC-code 15 01 04.

Remains of the product should be disposed of in accordance with regulations made by the local authorities: EWC-code 16 05 04.

### 14. Transport information

The product must be transported in accordance with national and/or international rules for transport of dangerous goods by road and sea according to ADR and IMDG.

**ADR:** UN 1950 ; AEROSOLS ; 2.1 ; - ; D

**IMDG:** UN 1950 ; AEROSOLS ; 2.1 ; -

Classification code: Label ADR: 2.1 Hazard identification number:

Flash point: °C Label IMDG: 2.1 IMDG EmS.: F-D, S-U

Revision: 15-02-2010/MJH  
Replaces: 10-11-2009

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 15. Regulatory information



Irritant



Extremely flammable



Dangerous for  
the environment

**Hazard designation:** Irritant; Extremely flammable; Dangerous for the environment

**Hazard symbols:** Xi;F+;N

#### R-phrases

Extremely flammable. (R12)

Irritating to skin. (R38)

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (R51/53)

Vapours may cause drowsiness and dizziness. (R67)

#### S-phrases

Keep away from sources of ignition - No smoking. (S16)

Wear suitable gloves. (S37)

Do not breathe vapour/spray. (S23)

Use only in well ventilated areas. (S51)

Avoid release to the environment. Refer to special instructions/safety data sheet. (S61)

#### Other labelling

Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Keep out of the reach of children.

#### Chemical safety assessment

Chemical safety assessment has not been performed.

Revision: 15-02-2010/MJH  
Replaces: 10-11-2009

## Kema HTSA-1400 High Temp. Stainless Anti-Seize Stainless Steel Paste Spray

### 16. Other information

#### Training requirement

No special training is required, but a thorough knowledge of this data safety sheet should be a prerequisite condition.

#### Packaging

Spray can.

#### Sources used

#### Other information

The product should only be used for the stated application or applications.

The information in this MSDS are based on our present state of knowledge and on current EEC and national laws. The users own working conditions are beyond our knowledge and control. The information in this MSDS are meant as a description of the safety requirements of our product: it may not be considered as a guarantee of the products' properties.

#### Full text of the R-phrases that are stated in section 3.

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### Amendments have been made in the following sections

1, 13, 14 and 16.

ITW Chemical Products Scandinavia Priorsvej 36, 8600 Silkeborg +45 86 82 64 44/+45 86 82 64 64 (Made in Toxido®) UK