



Safety data sheet

Kema GL-68 Slideway lubricant Spray

1. Identification of the substance/preparation and of the company/undertaking

Revision: 25-08-2010/ MP Replaces: 23-07-2009	Distributor: ITW Chemical Products Scandinavia Priorsvej 36 8600 Silkeborg
Product use: Slideway lubricant.	Tel: (+45) 86 82 64 44 Fax: (+45) 86 82 64 64 Emergency telephone number: +45 86 82 64 44 Emergency telephone number between 8 and 15.30 ; Monday to Friday. Contact person: Helle Nielsen Email: info@itw-scan.com
Article number: 22025	

2. Hazards identification

Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional information By prolonged use this product may form flammable/explosive vapour-air mixture. The vapour is heavier than air and can accumulate in low level areas. Prolonged or repeated inhalation of vapours may cause damage to the central nervous system. The product may cause slight transient irritation in the eyes.

3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	Classification	w/w%
265-150-3	64742-48-9	Naphtha (petroleum), hydrotreated heavy	Xn;R65 R66	1-5 3
265-151-9	64742-49-0	Naphtha (petroleum), hydrotreated light	F; R11 Xn;R65 Xi;R38 N;R51/53 R67	10-30 3
270-704-2	68476-85-7	Petroleum gases, liquefied (<0.1% 1,3-butadien)	F+;R12	10-30
-	-	Mineraloil, DMSO extract < 3% (IP 346)	None	10-30

3) R65 is not applicable due to use as aerosols.
Please see section 16 for the full text of the R-phrases

ITW Chemical Products Scandinavia Priorsvej 36, 8600 Silkeborg +45 86 82 64 44/+45 86 82 64 64

4. First aid measures

Inhalation

Seek fresh air. Seek medical advice if symptoms persist.

Ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Seek medical advice if symptoms persist.

Skin

Remove contaminated clothing. Wash skin with soap and water. Use a moisture cream. Seek medical advice if symptoms persist.

Eyes

Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice if symptoms persist. If irritation persists seek medical advice. (Bring this MSDS) Rinse the eyes during transportation.

Burns

Flush with water until pain ceases. Remove clothing that is not stuck to the skin – seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

Other information

When obtaining medical advice, show the safety data sheet or label.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water spray, as it may spread the fire. Use water or water mist to cool non-ignited stock. Remove larger stocks of containers from the danger area if this is possible without risk. Do not inhale vapours and flue gases - seek fresh air. Fire fighters should wear self-contained breathing apparatus.

6. Accidental release measures

In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Eliminate all sources of ignition. Spillage from aerosols is very unlikely. Provide adequate ventilation. Smoking and naked flames prohibited. Wipe up drops and splashes with a cloth and dispose of the cloth as set out in section 13. Use the same personal protective equipment as stated in section 8.

7. Handling and storage

Handling

Contains organic solvents. Ensure best possible ventilation. Please see item 8 for information on personal protection. Keep away from sources of ignition. No smoking.

Storage

Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C.

Revision: 25-08-2010/MP
Replaces: 23-07-2009

Kema GL-68 Slideway lubricant Spray

8. Exposure controls/ personal protection

Precautions for use

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment.

Respiratory protection

The product contains liquids with a low boiling point which are poorly adsorbed on charcoal filters. The use of fresh air respiratory protective equipment is thus required. In most cases a mask with a filter insert for hydrocarbon solvents is adequate, as the product normally is used only for a short period of time.

Gloves and protective clothing

Use chemical resistant gloves (e.g. 4H-gloves) in case of skin contact. Wear normal work wear.

Eye protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Ingredients	Exposure limit	Remarks
Petroleum gases, liquefied (<0.1% 1,3-butadien)	1000 ppm, 8h; 1250 ppm, 15min 1750 mg/m ³ , 8h; 2180 mg/m ³ , 15min	-

The exposure limits stated are in accordance with EH40/2002 Occupational Exposure Limits 2002.

Control methods

Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

9. Physical and chemical properties

Appearance: Colourless Liquid

Flash point: <0°C

Odour: Mild

Density: 0,71 g/mL

Solubility in water (g/100 ml): Not miscible

10. Stability and reactivity

Stabile under recommended storage and handling conditions. Durability for the aerosol is at least 5 years from date of production, if there is enough propellant in the aerosol to apply the contents in a satisfactory way. Reacts with strong oxidizing agents. Combustion will generate: Carbon monoxide (CO) and Carbon dioxide (CO₂).

11. Toxicological information

Acute

Inhalation

The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

Ingestion

Difficult because of the packing. May cause chemical pneumonia if ingested or vomited.

Skin contact

Prolonged skin contact can cause irritation.

Eye contact

May cause eye irritation.

Long-term effects

May cause damage to the central nervous system

Prolonged or repeated inhalation of vapours may cause damage to the central nervous system.

12. Ecological information

Avoid unnecessary release to the environment.

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Mobility

The product is insoluble in water. A part of the product is volatile and will evaporate from water and earth in a few days.

Persistence and degradability

The product is expected to be partially or slowly biodegradable.

Bioaccumulative potential

No bioaccumulation data provided.

13. Disposal considerations

Collect spills and waste in closed and sealed containers and send to the local disposal facility for chemical waste.

Remains of the product should be disposed of in accordance with regulations made by the local authorities: EWC-code 16 05 04. Empty aerosols (totally emptied for propellant) or aerosols that by accident have been punctured: EWC-code 15 01 04.

Revision: 25-08-2010/MP
Replaces: 23-07-2009

Kema GL-68 Slideway lubricant Spray

14. Transport information

The product must be transported in accordance with national and/or international rules for transport of dangerous goods by road and sea according to ADR and IMDG.

ADR: UN 1950 ; Aerosoler/Aerosols ; 2.1 ; ; D

IMDG: UN 1950 ; Aerosoler/Aerosols ; 2.1 ;

Classification code: 5F Label ADR: 2.1 Hazard identification number:

Flash point: < 0°C Label IMDG: 2.1 IMDG EmS.: F-D, S-U

15. Regulatory information



Hazard designation:

R-phrases

Extremely flammable. (R12A)

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (R52/53)

S-phrases

Keep away from sources of ignition - No smoking. (S16)

Take precautionary measures against static discharges. (S33)

Do not breathe vapour/spray. (S23-DA)

Use only in well ventilated areas. (S51)

Other labelling

Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Keep out of the reach of children.

Volatile organic compounds (VOC):

Chemical safety assessment

Chemical safety assessment has not been performed.

Revision: 25-08-2010/MP
Replaces: 23-07-2009

Kema GL-68 Slideway lubricant Spray

16. Other information

Restrictions on use

Training requirement

No special training is required, but a thorough knowledge of this data safety sheet should be a prerequisite condition.

Packaging

Spray can.

Sources used

Other information

The product should only be use for the stated application or applications.

The information in this MSDS are based on our present state of knowledge and on current EEC and national laws. The users own working conditions are beyond our knowledge and control. The information in this MSDS are meant as a description of the safety requirements of our product: it may not be considered as a guarantee of the products' properties.

Full text of the R-phrases that are stated in section 3.

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

ITW Chemical Products Scandinavia Priorsvej 36, 8600 Silkeborg +45 86 82 64 44/+45 86 82 64 64 (Made in Toxido®) UK